

NDS, Inc.
851 North Harvard Avenue
PO Box 339
Lindsay, California 93247
Toll Free (800) 726-1994
Toll Free Fax (800) 726-1998
Phone (559) 562-9888
Fax (559) 562-4488
Website www.ndspro.com
E-Mail nds@ndspro.com

March 2004

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, including *MasterFormat*, *SectionFormat*, and *PageFormat*, contained in the *CSI Manual of Practice*.

The section must be carefully reviewed and edited by the Architect to meet the requirements of the project and local building code. Coordinate this section with other specification sections and the Drawings.

Delete all "Specifier Notes" when editing this section.

SECTION 02934

ROOT BARRIER SHEET MATERIAL

Specifier Notes: This section covers NDS "Shawtown™ SM Series" root barrier sheet material. Consult NDS for assistance in editing this section for the specific application.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Root barrier sheet material.

1.2 RELATED SECTIONS

Specifier Notes: Edit the following list of related sections as required for the project. Provide section numbers. List other sections with work directly related to this section.

- A. Section 02_____ - Trees.

1.3 REFERENCES

Specifier Notes: List standards referenced in this section, complete with designations and titles. This article does not require compliance with standards, but is merely a listing of those used.

- A. ASTM D 256 - Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics.
- B. ASTM D 638 - Standard Test Method for Tensile Properties of Plastics.
- C. ASTM D 785 - Standard Test Method for Rockwell Hardness of Plastics and Electrical Insulating Materials.
- D. ASTM D 790 - Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials.

1.4 SUBMITTALS

- A. Comply with Section 01330 - Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including installation instructions.
- C. Samples: Submit manufacturer's 6-inch by 6-inch sample of root barrier sheet material.
- D. Warranty: Submit manufacturer's standard warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying product name and manufacturer.
- B. Storage: Store materials in clean, dry area protected from weather in accordance with manufacturer's instructions. Do not store materials in direct sunlight.
- C. Handling: Protect materials during handling and installation to prevent damage.

PART 2 PRODUCTS

2.1 MANUFACTURER

- A. NDS, Inc., 851 North Harvard Avenue, PO Box 339, Lindsay, California 93247. Toll Free (800) 726-1994. Toll Free Fax (800) 726-1998. Phone (559) 562-9888. Fax (559) 562-4488. Website www.ndspro.com. E-Mail nds@ndspro.com.

2.2 ROOT BARRIER SHEET MATERIAL

- A. Root Barrier Sheet Material: Shawtown SM Series root barrier sheet material.

Specifier Notes: Specify required root barrier sheet material. Delete sheet material not required.

1. 12-Inch High by 20-Foot Long SM Rolls: Part Number SM-1220.
2. 18-Inch High by 20-Foot Long SM Rolls: Part Number SM-1820.
3. 24-Inch High by 20-Foot Long SM Rolls: Part Number SM-2420.

4. 36-Inch High by 20-Foot Long SM Rolls: Part Number SM-3620.
5. 48-Inch High by 20-Foot Long SM Rolls: Part Number SM-4820.

B. Description:

1. 1-piece, without hinge-type sections.
2. Material: Up to 100 percent post-consumer, high-impact polystyrene (HIPS) with rubberizer added and UV inhibitor.
3. Thickness: Minimum 0.060 inch.
4. Connections: Solvent-welded H-couplings.
5. Reinforcing Ribs: 1/2-inch deep, raised vertical ribs running perpendicular to sheet, 6 inches on center.
6. Color: Black.

C. Physical Properties:

1. Tensile Stress, ASTM D 638: 3,800 psi.
2. Yield Elongation, ASTM D 638: 35 percent.
3. Flexural Modulus, ASTM D 790: 300,000 psi.
4. Notched Izod Impact, ASTM D 256: 2.0 psi at 73 degrees F.
5. Rockwell Hardness, ASTM D 785: L50.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine areas to receive root barrier sheet material. Notify Architect if areas are not acceptable. Do not begin installation until unacceptable conditions have been corrected.

3.2 INSTALLATION

- A. Install root barrier sheet material in accordance with manufacturer's instructions at locations indicated on the Drawings.

Specifier Notes: Specify linear/root pruning or surround application. Delete application not required.
--

- B. Linear/Root Pruning Application: Place root barrier sheet material directly adjacent to hardscape being protected.
- C. Surround Application: Place root barrier sheet material around root ball, at sufficient distance to allow proper backfill.
- D. Do not allow roots to circle or grow over top of root barrier sheet material.

END OF SECTION